

URW24 Universal Reel Winder Trailer



URW24 Skid Mount

Part Number 21032860/ 21032861 without Level Wind

STANDARD EQUIPMENT

- Front Plow Stabilizer
- Connecting Hoses Kit
40 ft (12 m) length
- 3 in (76 mm) Arbor bar
- Built in Level Wind
- Grounding Attachment
- Anchoring Points
- Wheel Chocks
- Safety Chains
- Storage Basket

OPTIONAL EQUIPMENT

- 21031775** Detachable Reel for Wire Recovery 75 x 45 in (1,905 x 1,143 mm)
- 21031760** Fixed Steel Reel for Wire Rope 75 x 45 in (1,905 mm x 1,143 mm)
- 21011815** Hydraulic Power Pack for Independent Operation

TRAILER SPECIFICATIONS

Net Weight w/o rope and reel	5,100 lbs (2,313 kg)
Overall Length	194 in (4,928 mm)
Overall Width	100 in (2,540 mm)
Height	125 in (3,175 mm)
Maximum GVWR	51,800 lbs (23,496 kg)
Brakes	Air
Electric System	12 V
Towing	Adjustable pintle eye

The Condux Tesmec URW24 Hydraulic Reel Winder Trailer is designed to work with the Condux Tesmec Pullers & Puller/ Tensioners, and operate as a separate winding system. It is equipped with an automatic level wind and negative self-acting hydraulic brake. The URW24 can be used with the following: The Condux Tesmec optional Fixed Steel reel, optional Detachable Reel or a Steel Conductor Reel.

Steel Conductor Reel Capacity:
90 x 45 in (2286 mm x 1143 mm)

21032659 URW24 Trailer Mounted

21032664 URW24 Trailer Mounted, without Level Wind



Hydraulic controls for complete control of the reel



Built in Level Wind

