

## 13 HP HYDRAULIC POWER PACK

### *Portable Hydraulic Power Pack*

This portable power source is matched perfectly to the power requirements of the Condux Tesmec reel stand and reel winders. See the chart below for specifications.

### GENERAL SPECIFICATIONS:

#### PERFORMANCE

Engine	13 HP
Fuel	Gas
Cooling	Air
Controls	Manual

#### CHARACTERISTICS

Frame Type	Two Wheel Mobile Unit
Length	26.5 in (673 mm)
Width	20 in (508 mm)
Height	27.5 in (698 mm)
Weight (Dry)	143 lbs (65 kg)

#### HYDRAULIC SYSTEM

Hyd. System	Open Center
Hydraulic Oil (Useable)	5 gallons/18.9 liters
Hydraulic Relief Valve Pressure	2,150 PSI (148 BAR)

#### HYDRAULIC RATED FLOW

GPM @ PSI	6.8	0	8.8	0
	5.9	1,800	8.0	2000
LPM @ BAR	25.8	0	33.3	0
	22.4	138	30.2	138



**ISO 9001:2015  
CERTIFIED**

**CONDUX | TESMEC**

Note: the basic machine performance is calculated at 68°F (20°C) and at sea level.



The latest issue of the Condux Tesmec Stringing Equipment & Accessories Catalog includes comprehensive product information specific for stringing applications in the transmission and distribution industries.



145 Kingswood Drive • Suite 1 • PO Box 668  
Mankato, MN 56002-0668 U.S.A.  
1-888-980-1209 Toll Free Phone (U.S. & Canada)  
1-507-387-8069 Phone  
info@conduxtesmec.com • www.conduxtesmec.com