

## CRT840 INSPECTION TROLLEY

### *Battery Powered Trolley*

The Condux Tesmec CRT840 Inspection Trolley is suitable for work on two, or three bundled conductors. The trolley is powered by four electric motors and an on-board battery. The unit provides easy lever and joystick control for speed, direction and brakes.

### GENERAL SPECIFICATIONS:

#### PERFORMANCE

Max speed	2.5 mph (4.0 km/h)
Max inclination	18°
Speed at maximum inclination	1.5 mph (2.5 km/h)
Autonomy	6 ÷ 8 span
Capacity	2.5 kN

#### CHARACTERISTICS

Conductors spacing	18 in (457 mm)
--------------------	----------------

#### POWER UNIT

Number of gearmotors	4
Total rated power	800 W
Electrical tension	24 V

#### SAFETY DEVICES

- Stationary brake voluntarily activated by operator
- Negative brake
- Footrest on the platform
- Anti-slippage floor
- Guard and protection on the rotating part

#### ADDITIONAL FEATURES

- Rubber wheel
- Lightweight aluminium frame
- Four lifting point
- Four Anchoring point on the side of the trolley

#### DIMENSIONS

Length	71 in (1800 mm)
Width	28.5 in (725 mm)
Height	63 in (1600 mm)
Total mass:	308 lb (140 kg) approx



**ISO 9001:2015**  
CERTIFIED

**CONDUX | TESMEC**

Note: the basic machine performance is calculated at 68°F (20°C) and at sea level.



The latest issue of the Condux Tesmec Stringing Equipment & Accessories Catalog includes comprehensive product information specific for stringing applications in the transmission and distribution industries.



145 Kingswood Drive • Suite 1 • PO Box 668  
Mankato, MN 56002-0668 U.S.A.  
1-888-980-1209 Toll Free Phone (U.S. & Canada)  
1-507-387-8069 Phone  
info@conduxtesmec.com • www.conduxtesmec.com